

Durasolve Primer HD

Optima Coatings Durasolve Primer HD is a fast-drying primer, compounded from the elastomeric tape adhesive. Surfaces to be primed prior to the application of Durapol Membranes.

Colours: Black

ADVANTAGES:

Durasolve Primer HD displays the following characteristics:
Promotes intimate contact between substrate and tape compound.
Promotes high adhesion.
Good wetting and penetration characteristics.
Can be applied by brush, roller or spray.

COMPOSITION:

A solvent based solution of polymer modified bitumen's.

SAFETY:

Durasolve Primer HD is flammable and should not be applied in the vicinity of naked flames or sources of ignition.
Avoid contact with the skin and the inhalation of vapours.
Always ensure adequate ventilation is provided.
Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating. Launder contaminated clothing, gloves, etc.

STORAGE:

Store in original containers in a cool, dry place away from and sources of ignition.

TYPICAL PROPERTIES

Solids Content
Specific Gravity
Spread Rate (clean steel)
Wet Film Thickness
Dry Film Thickness
Drying Time @ 23°C
Flash Point
Application Temperature Range

DATA

45%
0.92
7m²/lt
75-100µm
45-60µm
15-20 minutes
24°C minimum
0°C to 55°C

Technical details above are provided in good faith. We are an ISO 9001: 2008 registered company and our products are manufactured to the highest standards using raw materials of superior quality. Consequently we believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use. To retain sheen and colour consistency of your paint, always make sure that the batch numbers are the same on all paint containers that you purchase.

Updated: March 2013 (this supercedes all previous publications)